



# Labino® TrAc Pack Standard- UV



## POWERFUL | BATTERY OPERATED

## MAKES IT BRIGHT

- Labino® TrAc Pack Standard UV lamps have unbeatable UV intensity, creating extreme excitation of fluorescent material, which makes it possible to see things, in daylight and at great distances, that was once impossible with former technology.
- The Labino® TrAc Pack Standard is a two-part lamp consisting of a light weight luminary unit and a ballast unit (electronics and battery).
- The lamp is available in three important distinctions – floodlight, midlight or spotlight – each giving different beams and intensities.
- The lamp obtains full power in 5-15 seconds and can be switched on and off, without the need for pre-cooling.
- The lamp generates very little heat and is unaffected by magnetic fields.
- You can use the lamp outdoors, even in the rain, as the lamp is IP65 certified.
- Labino® TrAc Pack lamps are based on two key components – the Labino DUV-35 W Gas Discharge Bulb (MPXL technology) and the Labino Trigger Ballast (electronics). The interface technology between these key components creates unbeatable output performance.
- Manufactured in Sweden.



TrAc Pack Standard

## TECHNICAL SPECIFICATION

### Floodlight

Distribution angle (beam) approx. 45°  
Irradiance  $\approx 3\ 000\ \mu\text{W}/\text{cm}^2$  at 38 cm (15")

### Midlight

Distribution angle (beam) approx. 20°  
Irradiance  $\approx 8\ 000\ \mu\text{W}/\text{cm}^2$  at 38 cm (15")

### Spotlight

Distribution angle (beam) approx. 3.5°  
Irradiance  $\approx 45\ 000\ \mu\text{W}/\text{cm}^2$  at 38 cm (15")

### Voltage

- Charger: 100, 115, 230 VAC
- Internal Battery: 12/24 VDC
- Input Power: 43 W
- Output Power: 35 W

### Weight

- Luminary Unit: 1.2 kilos (2.6 lbs)
- Battery and Electronic Unit: 4.4 kilos (9.7 lbs)

### Cables

- Between Luminary and Battery/Electronic Unit: 2.3 meters (2.5 yd)

### Additional Information

- Mechanical Stability (bulb): IEC810
- Service life (bulb): approx. 2 000 hrs
- Wavelength: UV-A, peak at 365 nm
- Start-up time: full power after 5-15 sec
- Material in housing: anodized aluminium, plastics PA6-30
- The housing is via pre milled slots prepared for mounting devices
- S, CE, ETL, cETL approved
- IP65 classified, dust and temporary water jetting proof

### DISTRIBUTOR:

## TemaFlux srl

Via N. Tartaglia 11, Gussago (BS), Italy  
Tel +39 030 322079 – Fax +39 030 311872  
temaflux@temaflux.com – www.temaflux.com

### Battery

- 12 V, 7.2 Ampere, Lead
- Running time: 1.2 hours +/- 5%
- Charging time: 5-8 hours
- First time charge: 8 hours
- Charges from mains via wall socket charger
- Cannot be charged and operated at the same time

Labino AB shall not be held liable for any errors or omissions resulting from the test procedures that were used in validating performance of any Labino AB product nor for unforeseen errors or omissions in digital or printed material.